



Handling and maintenance

BCD 400 Heavy Duty Knot Filler gun

Technical Info

- Extra powerful gun, 400W for extra high industrial performance
- Internal temperature control between 140-230 °C.
- Applicator for Ø 12 mm sticks
- Ergonomic handle for long-term use in the production
- Unique trigger ensuring effortless adhesive application
- Reinforced design - Rubber cable with additional protection



The tool must be placed on the metal stand.



Never place the heated tool on its side.



Never point the nozzle upwards.

Caution!

The hot nozzle can cause damage and/or burns. After use, allow the gun to cool down completely before storing it. Keep safely and out of reach of children.

Please note the following handling points

- ✓ Let the gun heat for 3-4 minutes!
- ✓ Never pull a stick backwards from the gun.
- ✓ Recommended temperature setting 160-175 °C.
- ✓ Tighten the nozzle regularly.
- ✓ Use only recommended adhesives.
- ✓ Keep the melting chamber free of dirt and dust.
- ✓ Protect the device from moisture and liquids.



Internal temperature control between 140°-230° Celsius



Flow adjustment



Reinforced design with rubber cable and additional protection.

Empfohlene Betriebstemperatur: 160-175°C.



IMPORTANT!

Do not set the temperature above 195°C as this can damage the gun in the long term.